

SPANROCK XS

1. Unique identification code of the product-type:
RW-PL-G-0607-I
2. Type and serial number allowing identification of the product:
See product label **SPANROCK XS MW-EN 13162-T5-TR5**
3. Intended use of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer: **Thermal insulation products for buildings(ThIB)**
4. Name, registered trade name or trade mark and contact address of the manufacturer as required under article 11(5):
ROCKWOOL® Polska Sp. z o.o., ul.Kwiatowa 14, 66-131 Cigacice
5. Where, applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2): not applicable
6. System of attestation of conformity: **System1+ System 3**
7. Notified Certification body No. **1390 Centrum stavebního inženýrství a.s. Praha**, performed, carried out the initial type testing, the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of constancy of performance No **1390-CPR-0072/07/P (factory Cigacice)**; No **1390-CPR-0102/08/P (factory Małkinia)**.
8. Not applicable
9. Declared Performance in the Table 1 and Table 2

Table 1

Essential Characteristics	Clauses in this and other European standard(s) related to essential characteristics	Harmonized standard EN 13162:2012	Declared value / NPD ¹⁾
Reaction to fire	4.2.6 Reaction to fire	Euroclasses	A1
Release of dangerous substances to the indoor environment	4.3.13 Release of dangerous substances	EU level not yet available	c)
Acoustic absorption index	4.3.11 Sound absorption	α_p (AP ²⁾ and $\alpha_{w,0}$ (AW ²⁾ declared	NPD
Impact noise transmission index (for floors)	4.3.9 Dynamic stiffness	s' , SD ²⁾ declared	NPD
	4.3.10.2 Thickness, d_t	d_t declared and classes for thickness tolerances T6 or T7	NPD
	4.3.10.4 Compressibility c	CPI ²⁾ declared	NPD
	4.3.12 Air flow resistivity	AF ₁ ²⁾ declared. Direct airborne sound insulation index	NPD
Direct airborne sound insulation index	4.3.12 Air flow resistivity	AF ₁ ²⁾ declared.	NPD
Continuous glowing combustion	4.3.15 Continuous glowing combustion	EU level not yet available	b)
Thermal resistance	4.2.1 Thermal resistance and thermal conductivity	Declared R and λ , if possible	See table 2 0,041 W/mK
	4.2.3 Thickness	T ²⁾ class for thickness tolerance	T5
Water permeability	4.3.7.1 Short term water absorption	WS- declared $W_{s,0}$	NPD
	4.3.7.2 Long term water absorption	WL(P) -declared $W_{L,0}$	NPD
Water vapour permeability	4.3.8 Water vapour transmission	Declared μ : (MU ²⁾ or Z ²⁾	NPD
Compressive strength	4.3.3 Compressive stress or compressive strength	CS(10) ²⁾ or CS(10Y) ²⁾ declared	NPD
	4.3.5 Point load	PL(5) ²⁾ declared	NPD
Durability of reaction to fire against heat, weathering, ageing/degradation	4.2.7 Durability characteristics	Reaction to fire as declared by 4.2.6	not change with time
Durability of thermal resistance against heat, weathering, ageing/degradation	4.2.1 Thermal resistance and thermal conductivity	Declared R and λ , if possible	not change with time
	4.2.7 Durability characteristics	DS(70,-) declared The relative changes in thickness	NPD
	4.3.2 Dimensional stability under specified temperature or under specified temperature and humidity conditions	DS(70,90) declared The relative changes in thickness	NPD
Tensile strength	4.3.4 Tensile strength perpendicular to faces	TR ²⁾ declared	TR5
Durability of compressive strength against ageing/degradation	4.3.6 Compressive creep	CC(i_1 ²⁾ / i_2 ²⁾) σ_c compressive creep declared X_{c1} and X_{c2}	NPD

¹⁾ No performance determined; ²⁾ "-" indicates relevant class of level or declared value; ³⁾ national regulations not available; ⁴⁾ according to national regulations; see: Safety Use Instruction Sheet

Table 2

Thermal resistance, R_D														
d(mm)	50	60	70	80	90	100	110	120	130	140	150	160	170	180
R_D (m ² /KW)	1,20	1,45	1,70	1,95	2,15	2,40	2,65	2,90	3,15	3,40	3,65	3,90	4,10	4,35
d(mm)	190	200	210	220	230	240	-	-	-	-	-	-	-	-
R_D (m ² /KW)	4,60	4,85	5,10	5,35	5,60	5,85	-	-	-	-	-	-	-	-

NOTE: R value for thickness not seen in Table 2, is available on product label

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in Table 1 and Table 2 of point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Frank Christian Bartel
Technical&Production Director

(Name, function)

Cigacice, 10.01.2014

Place, date


Signature