

STALROCK MAX d=50-210mm

MW-EN 13162-T3-CS(10)0,5-WS-MU1

1. Unique identification code of the product-type:
RW-PL-G-0043-I
2. Intended use: Thermal insulation products for buildings (ThIB)
3. Manufacturer: ROCKWOOL® Polska Sp. z o.o.,
ul.Kwiatowa 14, 66-131 Cigacice
4. System of attestation of conformity: System1+ System 3
5. Harmonised standard: EN 13162:2012
Notified body No. 1390 Centrum stavebního inženýrství a.s. Praha
Certificate of constancy of performance No 1390-CPR-0072/07/P
(factory Cigacice).
6. Declared Performance in the Table 1 and Table 2.

Table 1

Essential Characteristics	Clauses in this and other European standard(s) related to essential characteristics	Harmonized standard EN 13162:2012	Declared value / NPD ¹⁾
Reaction to fire	4.2.6 Reaction to fire	Euroclasses	A1
Release of dangerous substances to the indoor environment	4.3.13 Release of dangerous substances	EU level not yet available	⁴⁾
Acoustic absorption index	4.3.11 Sound absorption	α_p (AP ²⁾) and α_w (AWI ³⁾) declared	NPD
Impact noise transmission index (for floors)	4.3.9 Dynamic stiffness	s' , SDI ⁴⁾ declared	NPD
	4.3.10.2 Thickness, d_L	d_L declared and classes for thickness tolerances T6 or T7	NPD
	4.3.10.4 Compressibility c	CPI ⁵⁾ declared	NPD
Direct airborne sound insulation index	4.3.12 Air flow resistivity	AFI ⁶⁾ declared. Direct airborne sound insulation index	NPD
	4.3.12 Air flow resistivity	AFI ⁶⁾ declared.	NPD
Continuous glowing combustion	4.3.15 Continuous glowing combustion	EU level not yet available	⁴⁾
Thermal resistance	4.2.1 Thermal resistance and thermal conductivity	Declared R and λ , if possible	See table 2 0,035 W/mK
	4.2.3 Thickness	T ⁷⁾ class for thickness tolerance	T3
	4.3.7.1 Short term water absorption	WS- declared W_p	$\leq 1 \text{ kg/m}^2$
Water permeability	4.3.7.2 Long term water absorption	WL(P)-declared W_p	NPD
	4.3.8 Water vapour transmission	Declared μ ; (MU ⁸⁾) or ZI ⁹⁾	MU1
Compressive strength	4.3.3 Compressive stress or compressive strength	CS(10) ¹⁰⁾ or CS(10Y) ¹¹⁾ declared	CS(10)0,5 kPa
	4.3.5 Point load	PL(5) ¹²⁾ declared	NPD
Durability of reaction to fire against heat, weathering, ageing/degradation	4.2.7 Durability characteristics	Reaction to fire as declared by 4.2.6	not change with time
Durability of thermal resistance against heat, weathering, ageing/degradation	4.2.1 Thermal resistance and thermal conductivity	Declared R and λ , if possible	not change with time
	4.2.7 Durability characteristics	DS(70,-) declared The relative changes in thickness	NPD
	4.3.2. Dimensional stability under specified temperature or under specified temperature and humidity conditions	DS(70,90) declared The relative changes in thickness	NPD
Tensile strength	4.3.4 Tensile strength perpendicular to faces	TR ¹³⁾ declared	NPD
Durability of compressive strength against ageing/degradation	4.3.6 Compressive creep	CC(t_1 , t_2) ¹⁴⁾ σ_c compressive creep declared X_d and X_t	NPD

¹⁾No performance determined; ²⁾"-" indicates relevant class of level or declared value; ³⁾national regulations not available; ⁴⁾according to national regulations; see: Safety Use Instruction Sheet

Table 2

d (mm)	Thermal resistance, R_0														
	50	100	110	120	130	140	150	160	170	180	185	190	200	210	-
R_0 (m ² /KW)	1,40	2,85	3,10	3,40	3,70	4,00	4,25	4,55	4,85	5,10	5,25	5,40	5,70	6,00	-

NOTE: R value for thickness not seen in Table 2, is available on product label

The performance of the product identified above is in conformity with the set of declared performance. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Frank Christian Bartel
Technical & Production Director
(Name, function)

Cigacice, 15.06.2015
Place, date

Signature