

ROOFROCK 30E d=50-250mm

MW-EN13162-T4-DS(70,-)-DS(70,90)-CS(10)30-TR7,5-PL(5)300-WS-WL(P)-MU1

1. Unique identification code of the product-type:
RW-CEE-0118
2. Intended use: **Thermal insulation products for buildings (ThIB).**
3. Manufacturer: **ROCKWOOL® Polska Sp. z o.o.,
ul.Kwiatowa 14, 66-131 Cigacice.**
4. System of attestation of conformity: **System 1 + System 3**
5. Harmonised standard: **EN 13162:2012+A1:2015**
Notified body No **1390 Centrum stavebního inženýrství a.s. Praha.**
Certificate of constancy of performance No **1390-CPR-0452/16/P (factory Cigacice), 1390-CPR-0097/08/P (factory Małkinia), 1390-CPR-0168/09/P (factory Bohumin).**
6. Declared Performance in the Table 1:

Table 1:

Essential Characteristics	Clauses in this and other European standard(s) related to essential characteristics	Harmonized standard EN 13162:2012+A1:2015	Declared value / NPD ¹⁾
Reaction to fire	4.2.6 Reaction to fire	Euroclasses	A1
Release of dangerous substances to the indoor environment	4.3.13 Release of dangerous substances	EU level not yet available	^{c)}
Acoustic absorption index	4.3.11 Sound absorption	α_p (AP ⁱ) and α_w , (AW ⁱ) declared	NPD
Impact noise transmission index (for floors)	4.3.9 Dynamic stiffness	s', SD ⁱ declared	NPD
	4.3.10.2 Thickness, d _L	d _L and classes for thickness tolerances T6 or T7	NPD
	4.3.10.4 Compressibility c	CP ⁱ declared	NPD
	4.3.12 Air flow resistivity	AF ⁱ declared	NPD
Direct airborne sound insulation index	4.3.12 Air flow resistivity	AF ⁱ declared	NPD
Continuous glowing combustion	4.3.15 Continuous glowing combustion	EU level not yet available	^{b)}
Thermal resistance	4.2.1 Thermal resistance and thermal conductivity	Thermal conductivity λ (W/mK)	0,036
		Thermal resistance R=d/ λ , (m ² K/W)	1,35 ÷ 6,90 see product label
	4.2.3 Thickness	Thickness range (mm)	50-250
Water permeability	4.3.7.1 Short term water absorption	WS- declared W _p ; (kg/m ²)	≤ 1
	4.3.7.2 Long term water absorption	WL(P) - declared W _{lp} ; (kg/m ²)	≤ 3
Water vapour permeability	4.3.8 Water vapour transmission	Declared μ ; (MU ⁱ) or Z ⁱ	MU1
Compressive strength	4.3.3 Compressive stress or compressive strength	CS(10) ⁱ or CS(10Y) ⁱ declared (kPa)	CS(10)30
	4.3.5 Point load	PL(5) ⁱ declared (N)	PL(5)300
Durability of reaction to fire against heat, weathering, ageing/degradation	4.2.7 Durability characteristics	²⁾ Euroclasses	A1
Durability of thermal resistance against heat, weathering, ageing/degradation	4.2.1 Thermal resistance and thermal conductivity	²⁾ declared R=d/ λ , (m ² K/W) and λ (W/mK) if possible	1,35 ÷ 6,90 see product label
		DS(70,-) declared The relative changes in thickness	≤1%
	4.2.7 Durability characteristics	DS(70,90) declared The relative changes in thickness	≤1%
Tensile strength	4.3.4 Tensile strength perpendicular to faces	TR ⁱ declared (kPa)	TR7,5
Durability of compressive strength against ageing/degradation	4.3.6 Compressive creep	CC(i_1 ^{a)} / i_2 ^{a)}) σ_c compressive creep declared X _{ct} and X _{ci}	NPD

¹⁾ No performance determined (NPD); ²⁾ no change with time; ^{a)} "i" indicates relevant class of level or declared value; ^{b)} national regulations not available; ^{c)} according to national regulations; see: Safety Use Instruction Sheet;

The performance of the product identified above is in conformity with the set of declared performance. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Frank Christian Bartel
Technical & Production Director
(Name, function)
Cigacice, 05.09.2016
(Place, date)


(Signature)