

## Declaration of Performance No RW-CEE-DoP-0800/C/17/w1

- |   |   |
|---|---|
| <p><b>1.</b> Unique identification code of the product-type:<br/><b>RW-CEE-0800</b></p> <p><b>2.</b> Intended use: <b>thermal insulation products for building equipment.</b></p> <p><b>3.</b> Manufacturer: <b>ROCKWOOL Polska Sp. z o.o.</b><br/><b>ul.Kwiatowa 14, 66-131 Cigacice</b></p> | <p><b>4.</b> System of attestation of conformity: <b>System 1 and System 3</b></p> <p><b>5.</b> Harmonised standard: <b>EN 14303:2009+A1:2013</b><br/>Notified body No. <b>1390 Centrum stavebního inženýrství a.s. Praha.</b></p> <p><b>6.</b> Declared Performance in the Table 1:<br/><b>MW-EN 14303-T4-ST(+)250-WS1-MV2</b></p> |
|---|---|

Table 1

Essential characteristics		Performance	Declared value/ NPD <sup>1)</sup>				Harmonized technical specification
Thermal resistance	Thermal conductivity	Temperature $\vartheta$ (°C)	10	50	150	250	EN 14303:2009+A1:2013
		Thermal conductivity $\lambda_D$ W/(m·K)	0,039	0,050	0,083	0,134	
	Thickness	Thickness $d_D$ mm Ti <sup>2)</sup> thickness tolerances	20-100 T4				
Reaction to fire		Euroclass – reaction to fire (RtF):	A1				
Durability of thermal resistance against ageing/degradation		Maximum service temperature 250°C	ST(+) 250				
Durability of thermal resistance against high temperature		Maximum service temperature 250°C	ST(+) 250				
Durability of reaction to fire against ageing/ degradation		Durability characteristics - reaction to fire (RtF)	A1				
Durability of reaction to fire against high temperature		Durability characteristics - reaction to fire (RtF)	A1				
Compressive strength		Compressive strength at 10% deformation CS(10)i <sup>2)</sup>	NPD				
Water permeability		Water absorption ( $\leq 1$ kg/m <sup>2</sup> )	WS1				
Water vapour permeability		Water vapour diffusion equivalent air layer thickness, MV <sup>2)</sup>	MV2				
Rate of release of corrosive substances		Trace quantities of water-soluble chloride ions (ppm) pHi <sup>2)</sup> -value	NPD NPD				
Acoustic absorption index		Sound absorption (AWi <sup>a)</sup> )	NPD				
Release of dangerous substances		Release of dangerous substances	NPD				
Continuous glowing combustion		Continuous glowing combustion	NPD				

<sup>1)</sup> No performance determined; <sup>2)</sup> "i" indicates relevant class of level or declared value;

This declaration of performance is available on the website [dop.rockwool.com](http://dop.rockwool.com)

The performance of the product identified above is in conformity with the set of declared performance. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

**Halina Ozon**  
Central Service Department Manager  
(Name, function)

**Cigacice dn. 15.01.2018**  
(Place, date)

  
(Signature)