

## Declaration of Performance No RW-CEE-DoP-0826/C/18/w1

- |  |   |
|--|---|
| <p>1. Unique identification code of the product-type:<br/><b>RW-CEE-0826</b></p> <p>2. Intended use: <b>thermal insulation products for building equipment.</b></p> <p>3. Manufacturer: <b>ROCKWOOL Polska Sp. z o.o.</b><br/><b>ul.Kwiatowa 14, 66-131 Cigacice</b></p> | <p>4. System of attestation of conformity: <b>System 1 and System 3</b></p> <p>5. Harmonised standard: <b>EN 14303:2009+A1:2013</b><br/>Notified body No. <b>1390 Centrum stavebního inženýrství a.s. Praha.</b></p> <p>6. Declared Performance in the Table 1:<br/> d&lt;60 mm      <b>MW-EN 14303-T3-ST(+)250-WS1</b><br/> d≥60 mm      <b>MW-EN 14303-T4-ST(+)250-WS1</b><br/> d=100 mm      <b>MW-EN 14303-T4-ST(+)250-AW1,00-WS1</b></p> |
|--|---|

Table 1

Essential characteristics		Performance	Declared value/ NPD <sup>1)</sup>			Harmonized technical specification
Thermal resistance	Thermal conductivity	Temperature $\vartheta$ (°C)	50	150	250	EN 14303:2009+A1:2013
		Thermal conductivity $\lambda_D$ W/(m·K)	0,041	0,062	0,093	
	Thickness	Thickness $d_D$ mm Ti <sup>2)</sup> thickness tolerances: $d_D < 60$ mm $d_D \geq 60$ mm	25-100 T3 T4			
Reaction to fire		Euroclass – reaction to fire (RtF):	A1			
Durability of thermal resistance against ageing/degradation		Maximum service temperature 250°C	ST(+)250			
Durability of thermal resistance against high temperature		Maximum service temperature 250°C	ST(+)250			
Durability of reaction to fire against ageing/ degradation		Durability characteristics - reaction to fire (RtF)	A1			
Durability of reaction to fire against high temperature		Durability characteristics - reaction to fire (RtF)	A1			
Compressive strength		Compressive strength at 10% deformation CS(10) <sup>i2)</sup>	NPD			
Water permeability		Water absorption ( $\leq 1$ kg/m <sup>2</sup> )	WS1			
Water vapour permeability		Water vapour diffusion equivalent air layer thickness, MVi <sup>2)</sup>	NPD			
Rate of release of corrosive substances		Trace quantities of water-soluble chloride ions (ppm) pHi <sup>2)</sup> -value	NPD NPD			
Acoustic absorption index		Sound absorption (AWi <sup>3)</sup> ) for $d_D=100$ mm	AW1,00			
Release of dangerous substances		Release of dangerous substances	NPD			
Continuous glowing combustion		Continuous glowing combustion	NPD			

<sup>1)</sup> No performance determined; <sup>2)</sup> "\*" indicates relevant class of level or declared value;

This declaration of performance is available on the website [dop.rockwool.com](http://dop.rockwool.com)

The performance of the product identified above is in conformity with the set of declared performance. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

**Halina Ozon**  
Central Service Department Manager  
(Name, function)

**Cigacice dn. 21.01.2018**  
(Place, date)

  
(Signature)