

1. Unique identification code of the product-type: **ROCKWOOL UNDERPUDS**
2. Type and serial number allowing identification of the product: See product label
3. Intended use of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer: ROCKWOOL UNDERPUDS is to be used for fixing mineral wool boards and mesh embedding.
4. Name, registered trade name or trade mark and contact address of the manufacturer as required under article 11(5):
ROCKWOOL A/S, Hovedgaden 501, DK-2640 Hedehusene
5. System of attestation of conformity: System 4
6. In accordance with EN 998-1:2010, research report no BT1/SpW/2013.
7. Declared Performance:

| Essential Characteristics EN 998-1:2010 | Performance | Levels and/or classes | Notes/ declaration |
|--|--------------------------------|---|---|
| Reaction to fire | Reaction to fire | A1 | EN 13501-1, Declaration as in EN 998-1, p.5.2.2 |
| Hygiene, health and the environment | Water absorption | W2 | EN 1015-18 |
| | Water vapour permeability | 5/20 | EN 1745 |
| | Thermal conductivity / density | 0,47 [W/mK] P=50% | EN 1745:2002, 4.2.2 |
| | Dangerous substances | The chromium (VI) ≤ 0,0002 | EN 998-1 ZA.1 |
| Safety and accessibility in use | Compressive strength | category CSIV (> 6 N/mm ²) | EN 998-1: 5.2.3.1 and EN 1015-11 ^a |
| | Adhesion | ≥ 0,25, FP:B | EN 1015-12 |

8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7. This declaration of performance is issued under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Technical Director Klaus Hovmøller



Hedehusene, June 25th 2013