

1. Unique identification code of the product-type: **ROCKWOOL STRUKTURPUDS 1.0/1.5/2.0 SIL**
2. Type and serial number allowing identification of the product: See product label
3. Intended use of the construction product, in accordance with the applicable harmonized technical specification as foreseen by the manufacturer: ROCKWOOL STRUKTURPUDS 1.0/1.5/2.0 SIL is intended for manual application of stucco, thin-layer plaster indoors and outdoors. It can be applied on any sufficiently firm and even mineral substrate (cement plasters, cement- lime plasters, concrete, sandstone) and covered with well-adhering paint coating.
4. Name, registered trade name or trade mark and contact address of the manufacturer as required under article 11(5):
ROCKWOOL A/S, Hovedgaden 501, DK-2640 Hedehusene
5. System of attestation of conformity: System 3
6. In accordance with EN 15824:2009 PAVUS, a.s., Prosecka 412/74, CZ 190 00, Praha9-Prosek, notified body nr 1391, carried out the initial test of reaction to fire and issued a research report nr: PK1-01-13-069-A-0.
7. Declared Performance:

Essential Characteristics EN 998-1:2010	Performance	Levels and/or classes	Notes/ declaration
Reaction to fire	Reaction to fire	A2/s1/d0	EN 13501-1
Hygiene, health and the environment	Water absorption	W2	EN 1062-3
	Water vapour permeability	V1	EN ISO 7783-2
	Thermal conductivity / density	0,83 [W/mK] P=50%	EN 1745
	Dangerous substances	According to ZA.3	EN 15824
Safety and accessibility in use	Adhesion	≥ 0,3 MPa	EN 1542
	Durability	NPD	EN 13687-3

8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7. This declaration of performance is issued under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Technical Director Klaus Hovmøller



Hedehusene, June 25th 2013