


1. Unique identification code of the product-type: **ROCKWOOL KORNPUDS 2.0**
2. Type and serial number allowing identification of the product: See product label
3. Intended use of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer: ROCKWOOL KORNPUDS 2.0 is designed for manual thin-coat stucco plaster work as both an interior and exterior finish. It can be applied on any mineral sufficiently firm and even mineral substrate (cement plasters, cement-lime plasters and concrete).
4. Name, registered trade name or trade mark and contact address of the manufacturer as required under article 11(5):
ROCKWOOL A/S, Hovedgaden 501, DK-2640 Hedehusene
5. System of attestation of conformity: System 4
6. In accordance with EN 998-1:2010, research report no BT1/TMK/2009
7. Declared Performance:

Essential Characteristics EN 998-1:2010	Performance	Levels and/or classes	Notes/ declaration
Reaction to fire	Reaction to fire	A1	EN 13501-1, Declaration as in EN 998-1, p.5.2.2
Hygiene, health and the environment	Water absorption	W2	EN 1015-18
	Water vapour permeability	≤ 15	EN 1015-19 ^{ab}
	Thermal conductivity / density	0,67 [W/mK] P=50%	EN 1745 Tabular value-tab. A12
	Dangerous substances	The chromium (VI) ≤ 0,0002	EN 998-1 ZA.1
Safety and accessibility in use	Compressive strength	category CSIV (1,5-5,0 N/mm ²)	EN 998-1: 5.2.3.1 and EN 1015-11 ^a
	Adhesion	min. 0,3, FP:B	EN 1015-12

8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7. This declaration of performance is issued under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Technical Director Klaus Hovmøller



Hedehusene, June 25th 2013