

VENTI MAX / WENTIROCK MAX

- Unique identification code of the product-type:
RW-PL-G-0055-I
- Type and serial number allowing identification of the product:
**See product VENTI MAX / WENTIROCK MAX
MW-EN 13162-T3-CS(10)0,5-WS-MU1**
- Intended use of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer: **Thermal insulation products for buildings(ThIB)**
- Name, registered trade name or trade mark and contact address of the manufacturer as required under article 11(5):
ROCKWOOL® Polska Sp. z o.o., ul.Kwiatowa 14, 66131 Cigacice.
- Where, applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2): not applicable
- System of attestation of conformity: **System1+ System 3**
- Notified Certification body No. 1390 Centrum stavebního inženýrství a.s. Praha, performed, carried out the initial type testing, the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of constancy of performance **No 1390-CPR-0296/11/P (factory Bohumin).**
- Not applicable
- Declared Performance in the Table 1 and Table 2

Table 1

| Essential Characteristics | Clauses in this and other European standard(s) related to essential characteristics | Harmonized standard EN 13162:2012 | Declared value / NPD ¹⁾ |
|---|--|--|------------------------------------|
| Reaction to fire | 4.2.6 Reaction to fire | Euroclasses | A1 |
| Release of dangerous substances to the indoor environment | 4.3.13 Release of dangerous substances | EU level not yet available | c) |
| Acoustic absorption index | 4.3.11 Sound absorption | α_p (AP ²⁾ and α_w (AW ²⁾ declared | NPD |
| Impact noise transmission index (for floors) | 4.3.9 Dynamic stiffness | s' , SD ²⁾ declared | NPD |
| | 4.3.10.2 Thickness, d_L | d_L declared and classes for thickness tolerances T6 or T7 | NPD |
| | 4.3.10.4 Compressibility c | CPI ²⁾ declared | NPD |
| | 4.3.12 Air flow resistivity | AF _i ²⁾ declared. Direct airborne sound insulation index | NPD |
| Direct airborne sound insulation index | 4.3.12 Air flow resistivity | AF _i ²⁾ declared. | NPD |
| Continuous glowing combustion | 4.3.15 Continuous glowing combustion | EU level not yet available | b) |
| Thermal resistance | 4.2.1 Thermal resistance and thermal conductivity | Declared R and λ if possible | See table 2 0,034 W/mK |
| | 4.2.3 Thickness | T ²⁾ class for thickness tolerance | T3 |
| | 4.3.7.1 Short term water absorption | WS- declared W_{sP} | $\leq 1 \text{ kg/m}^2$ |
| Water permeability | 4.3.7.2 Long term water absorption | WL(P)-declared W_{Lp} | NPD |
| | 4.3.8 Water vapour transmission | Declared μ ; (MU ²⁾ or ZI ²⁾ | MU1 |
| Compressive strength | 4.3.3 Compressive stress or compressive strength | CS(10) ²⁾ or CS(10Y) ²⁾ declared | CS(10)0,5 kPa |
| | 4.3.5 Point load | PL(5) ²⁾ declared | NPD |
| Durability of reaction to fire against heat, weathering, ageing/degradation | 4.2.7 Durability characteristics | Reaction to fire as declared by 4.2.6 | not change with time |
| Durability of thermal resistance against heat, weathering, ageing/degradation | 4.2.1 Thermal resistance and thermal conductivity | Declared R and λ if possible | not change with time |
| | 4.2.7 Durability characteristics | DS(70.-) declared The relative changes in thickness | NPD |
| | 4.3.2 Dimensional stability under specified temperature or under specified temperature and humidity conditions | DS(70.90) declared The relative changes in thickness | NPD |
| Tensile strength | 4.3.4 Tensile strength perpendicular to faces | TRI ²⁾ declared | NPD |
| Durability of compressive strength against ageing/degradation | 4.3.6 Compressive creep | CC(l_1 ²⁾ / l_2 ²⁾) σ_c compressive creep declared X_{c1} and X_c | NPD |

¹⁾ No performance determined; ²⁾ " indicates relevant class of level or declared value; ^{b)} national regulations not available; ^{c)} according to national regulations; see: Safety Use Instruction Sheet

Table 2

| | | Thermal resistance, R_D | | | | | | | | | | | | | |
|-----------------------------|--|---------------------------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| d(mm) | | 30 | 40 | 50 | 60 | 70 | 80 | 90 | 100 | 110 | 120 | 130 | 140 | 150 | 160 |
| $R_D(\text{m}^2\text{K/W})$ | | 0,85 | 1,15 | 1,45 | 1,75 | 2,05 | 2,35 | 2,60 | 2,90 | 3,20 | 3,50 | 3,80 | 4,10 | 4,40 | 4,70 |
| d(mm) | | 170 | 180 | 190 | 200 | - | - | - | - | - | - | - | - | - | - |
| $R_D(\text{m}^2\text{K/W})$ | | 5,00 | 5,25 | 5,55 | 5,85 | - | - | - | - | - | - | - | - | - | - |

NOTE: R value for thickness not seen in Table 2, is available on product label

- The performance of the product identified in points 1 and 2 is in conformity with the declared performance in Table 1 and Table 2 of point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Frank Christian Bartel
Technical&Production Director
(Name, function)

Cigacice, 0.09.2014
Place, date

Signature