FS2 Universal Mortar – general purpose (GP) mortar

http://dop.rockwool.com

1.	Unique identification code of the product-type	UK-WER-0122-01_english
2.	Intended use of the construction product as foreseen by the manufacturer, in accordance with the applicable harmonised technical specification	FS2 Universal Mortar is to be used for fixing mineral wool boards and mesh embedding
3.	Name, registered trade name or registered trade mark and contact address of the manufacturer, as required pursuant to Article 11(5) of regulation (EU) No 305/2011	ROCKWOOL® Limited Pencoed, Bridgend, CF35 6NY
4.	Applicable System or Systems of Assessment and Verification of Constancy of Performance (AVCP)	System 4
5.	Harmonised Standard reference number Date of issue Research Report number	EN 998-1: 2010 28 February 2011 BT1/NW/2013
6.	Notified Body identification number Notified Body research report number	1391 PK1-01-13-073-A-0
7.	Declared Performances	Please refer to the table below (NPD – No Performance Determined)

Essential Characteristics	Requirement clauses in this European Standard	Level and/or classes	Notes / Type of Declaration
Reaction to fire	Reaction to fire	A1	EN 13501-1, Declaration as in EN 998-1, p.5.2.2
Hygiene, health and the environment	Water aborption	W2	EN 1015-18
	Water vapour permeability	≤ 15	EN 1745: 2002 Tabular value tab.A12
	Thermal conductivity / density	0.67 (W/mK) P=50%	EN 1745:2002, 4.2.2
	Dangerous substances	The chromium (VI) ≤ 0.0002	EN 998-1: ZA.1
Safety and accessibility in use	Compressive strength	category CSIV (>6 N/mm2)	EN 998-1: 5.2.3.1 as in EN 1015-11
	Adhesion	≥ 0.25 FP:B	EN 1015-12

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Bob PERRY Production Director

At Bridgend on 20th July 2014