

1. Unique identification code of the product-type	UK-WER-0127-01_english
2. Intended use of the construction product as foreseen by the manufacturer, in accordance with the applicable harmonised technical specification	Silicone render is intended for manual application of stucco, thin-layer plaster indoors and outdoors. It can be applied on any sufficiently firm and even mineral substrate (cement plasters, cement-lime plasters, concrete and sandstone) and covered with well-adhering paint coating
3. Name, registered trade name or registered trade mark and contact address of the manufacturer, as required pursuant to Article 11(5) of regulation (EU) No 305/2011	ROCKWOOL® Limited Pencoed, Bridgend, CF35 6NY
4. Applicable System or Systems of Assessment and Verification of Constancy of Performance (AVCP)	System 3
5. Harmonised Standard reference number Date of issue	EN 15824: 2009 31 October 2009
6. Notified Body identification number Notified Body research report number	1391 PK1-01-13-073-A-0
7. Declared Performances	Please refer to the table below (NPD – No Performance Determined)

Essential Characteristics	Requirement clauses in this European Standard	Level and/or classes	Notes / Type of declaration
Reaction to fire	Reaction to fire	A2-s1,d0	EN 13501-1
Hygiene, health and the environment	Water vapour permeability	V1	EN ISO 7783-2
	Water absorption	W2	EN 1062-3
	Thermal conductivity	0.83 (P=50%) [W/mK] tabular value	EN 1745
	Dangerous substances	According to ZA.3	EN 15824
Safety and accessibility in use	Adhesion	≥ 0.3 Mpa	EN 1542
	Durability	NPD	EN 13687-3

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Bob PERRY  
Production Director



At Bridgend on 20th July 2014