

Declaration of Performance No: RWDOPBNL-999-010-01

1. Unique identification code of the product-type: RockFloor Extra
2. Type and serial number allowing identification of the product: see product label
3. Intended use of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer: Thermal insulation of buildings.
4. Name, registered trade name or trade mark and contact address of the manufacturer as required under article 11(5): DEUTSCHE ROCKWOOL Mineralwol GmbH & Co. OHG, Rockwool Strasse 37-41, 45966 Gladbeck, Deutschland
5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2): ROCKWOOL B.V., Industrieweg 15, 6045 JG Roermond (NL)
6. Systems of assessment and verification of constancy of performance of the construction as set out in CPR, Annex V: 1+3
7. Notified Certification body No. 0432 performed, carried out the determination of the product type, the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of constancy of performance for reaction to fire.
Notified testing laboratories No. 0432 performed the test reports for the other relevant declared characteristics.
8. Declared Performance:

Essential Characteristics	Clauses in this and other European standard(s) related to essential characteristics	Harmonized standard EN 13162:2012+A1 2015	Declared value / NPD
Reaction to fire	4.2.6 Reaction to fire	Euroclasses	A1
Release of dangerous substances to the indoor environment	4.3.13 Release of dangerous substances	–	European test method under construction
Acoustic absorption index	4.3.11 Sound absorption	Declared α_p and α_w	NPD
Impact noise transmission index (for floors)	4.3.9 Dynamic stiffness	Declared S [MN/m ³]	20 mm: 48, 30 mm: 27 40 mm: 21
	4.3.10.2 Thickness, d_L	Declared d_L [mm] and Class	T7
	4.3.10.4 Compressibility c	Declared CP Level	CP2
	4.3.12 Air flow resistivity	Direct airborne sound insulation index, Declared AF_r [kPas/m ²]	AF _r 43
Direct airborne sound insulation index	4.3.12 Air flow resistivity	Declared AF_r [kPas/m ²]	AF _r 43
Continuous glowing combustion	4.3.15 Continuous glowing combustion	–	European test method under construction
Thermal resistance	4.2.1 Thermal resistance and thermal conductivity	Declared R [m ² K/W] and λ [W/mK] if possible	See annex Ad: 0,035
	4.2.2 Length and width	Declared l and b	Tolerance: l \pm 2% / b \pm 1.5%
	4.2.3 Thickness	Declared d or tolerance class	Thickness: 20-40 mm Tolerance class: T7
	4.2.4 Squareness	Declared S_b [mm/m]	n.a.
	4.2.5 Flatness	Declared S_{max} [mm]	n.a.
Water permeability	4.3.7.1 Short term water absorption	Declared W_p [kg/m ²]	NPD
	4.3.7.2 Long term water absorption	Declared W_{lp} [kg/m ²]	NPD
Water vapour permeability	4.3.8 Water vapour transmission	Declared μ or Z	$\mu=1$
Compressive strength	4.3.3 Compressive stress or compressive strength	Declared CS [kPa]	NPD
	4.3.5 Point load	Declared F_p [N]	NPD
Durability of reaction to fire against heat, weathering, ageing/degradation	4.2.7 Durability characteristics ^{a)}	^{b)}	^{a), b)}
Durability of thermal resistance against heat, weathering, ageing/degradation	4.2.1 Thermal resistance and thermal conductivity	Declared R [m ² K/W] and λ [W/mK] if possible ^{c)}	See annex Ad: 0,035
	4.2.7 Durability characteristics	^{d)}	NPD
Tensile/Flexural strength	4.3.4 Tensile strength perpendicular to faces ^{e)}	Declared TR [kPa]	NPD
Durability of compressive strength against ageing/degradation	4.3.6 Compressive creep	Declared X_{ct} and X_t	NPD


^{a)}No change in reaction to fire properties for mineral wool products. ^{b)}The fire performance of mineral wool does not deteriorate with time. The Euroclass classification of the product is related to the organic content, which cannot increase with time. ^{c)}Thermal conductivity of mineral wool products does not change with time, experience has shown the fibre structure to be stable and the porosity contains no other gases than atmospheric air. ^{d)}For dimensional stability thickness only. ^{e)}This characteristic also covers handling and installation.

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by (digital signature):

W.J.E. Dumoulin
Technical Director

Roermond, January 15th 2017



Thickness (mm)	$R_d(m^2K/W)$
20	0.55
25	0.70
30	0.85
35	1.00
40	1.10