

## DECLARATION OF PERFORMANCE

### No RW-CEE-DoP-0170/CM/18/w1

- |                                                                                                                                                                                                                                                                                   |                                                                                                                                                                                                                                                                                                                                             |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <p><b>1.</b> Unique identification code of the product-type:<br/><b>RW-CEE-0170</b></p> <p><b>2.</b> Intended use: Thermal insulation products for buildings (ThIB).</p> <p><b>3.</b> Manufacturer: <b>ROCKWOOL® Polska Sp. z o.o.</b>,<br/>ul. Kwiatowa 14, 66-131 Cigacice.</p> | <p><b>4.</b> System/s of AVCP: <b>System 1 and System 3</b></p> <p>Harmonised standard: <b>EN 13162:2012+A1:2015</b></p> <p><b>5.</b> Notified body No <b>1390 Centrum stavebního inženýrství a.s. Praha.</b></p> <p><b>6.</b> Declared Performance in the Table 1 and Table 2:<br/><b>MW-EN 13162-T3-CS(10)0,5-WS-WL(P)-AW0,90-MU1</b></p> |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

**Table 1**

Essential Characteristics	Performance	Declared value / NPD <sup>1)</sup>	Harmonized technical specification
Thermal resistance	Thermal resistance $R_0$ and $d_N$ thermal conductivity $\lambda_D$	see Table 2 0,035 W/mK	EN 13162:2012+A1:2015
	Ti <sup>a)</sup> Thickness	T3	
Reaction to fire	Euroclasses – Reaction to fire (RtF) product	A1	
Durability of reaction to fire against heat, weathering, ageing/ degradation <sup>2)</sup>	Durability characteristics Reaction to fire (RtF) product	A1	
Durability of thermal resistance against heat, weathering, ageing/ degradation <sup>2)</sup>	Thermal resistance $R_0$ and thermal conductivity $\lambda_D$ (W/mK)	see Table 2 0,035 W/mK	
	Durability characteristics	NPD	
Compressive strength	Compressive stress CS(10) <sup>3)</sup> , CS(10/Y) <sup>3)</sup> (kPa)	CS(10)0,5	
	Point load PL(5) <sup>3)</sup> (N)	NPD	
Tensile / Flexural strength	Tensile strength perpendicular to faces TR <sup>3)</sup> (kPa)	NPD	
Durability of compressive strength against ageing/ degradation	Compressive creep	NPD	
Water permeability	Short term water absorption WS ( $\leq 1$ kg/m <sup>2</sup> )	WS	
	Long term water absorption WL(P) ( $\leq 3$ kg/m <sup>2</sup> )	WL(P)	
Water vapour permeability	Water vapour transmission Water vapour diffusion resistance factor	MU1	
Impact noise transmission index (for floors)	Dynamic stiffness SD <sup>3)</sup> Thickness, $d_i$ Compressibility $c$ Air flow resistivity AFri <sup>3)</sup>	NPD NPD NPD NPD	
Acoustic absorption index	Sound absorption AW <sup>3)</sup>	AW0,90	
Direct airborne sound insulation index	Air flow resistivity AFri <sup>3)</sup>	NPD	
Continuous glowing combustion	Continuous glowing combustion	NPD	
Release of dangerous substances to the indoor environment	Release of dangerous substances to the indoor environment	NPD	

<sup>1)</sup> No performance determined (NPD); <sup>2)</sup> no change with time; <sup>3)</sup> "i" indicates relevant class of level or declared value;

**Table 2**

$d_N$ (mm)	50	60	70	80	-	-	-	-	-	-	-	-	-	-	-	-	-
$R_0$ (m <sup>2</sup> K/W)	1,40	1,70	2,00	2,25	-	-	-	-	-	-	-	-	-	-	-	-	-

This declaration of performance is available on the website [dop.rockwool.com](http://dop.rockwool.com)

The performance of the product identified above is in conformity with the set of declared performance. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

**Halina Ozon**  
Central Service Department Manager  
(Name, function)

**Cigacice 03.09.2018**  
(Place, date)

*Halina Ozon*  
.....  
(Signature)