

DECLARATION OF PERFORMANCE

No RW-CEE-DoP-0669/B/20/w1

- | | |
|---|---|
| 1. Unique identification code of the product-type:
RW-CEE-0669 | 4. System/s of AVCP: System 1 and System 3
Harmonised standard: EN 13162:2012+A1:2015 |
| 2. Intended use/es: Thermal insulation products for buildings (ThIB). | 5. Notified body No 1390 ITC Divize CSI - Centrum stavebního inženýrství |
| 3. Manufacturer: ROCKWOOL® Polska Sp. z o.o.,
ul. Kwiatowa 14, 66-131 Cigacice. | 6. Declared Performance/s: in the Table 1 and Table 2: |

Table 1

Essential Characteristics	Performance	Declared value / NPD ¹⁾	Harmonized technical specification
Thermal resistance	Thermal resistance R_0 and d_{λ} thermal conductivity λ_D Ti ^{a)} Thickness	see Table 2 0,036 W/mK T3	EN 13162:2012+A1:2015
Reaction to fire	Euroclasses – Reaction to fire (RtF) product	A1	
Durability of reaction to fire against heat, weathering, ageing/ degradation	Durability characteristics Reaction to fire (RtF) product ²⁾	A1	
Durability of thermal resistance against heat, weathering, ageing/ degradation	Thermal resistance R_0 and thermal conductivity λ_D (W/mK) ²⁾ Durability characteristics	see Table 2 0,036 W/mK NPD	
Compressive strength	Compressive stress CS(10) ^{a)} , CS(10/Y) ^{a)} (kPa) Point load PL(5) ^{a)} (N)	NPD NPD	
Tensile / Flexural strength	Tensile strength perpendicular to faces TR ^{a)} (kPa)	NPD	
Durability of compressive strength against ageing/ degradation	Compressive creep	NPD	
Water permeability	Short term water absorption WS (≤ 1 kg/m ²) Long term water absorption WL(P) (≤ 3 kg/m ²)	NPD NPD	
Water vapour permeability	Water vapour transmission Water vapour diffusion resistance factor	MU1	
Impact noise transmission index (for floors)	Dynamic stiffness SD ^{a)} Thickness, d_L Compressibility c Air flow resistivity AFR ^{a)}	NPD NPD NPD NPD	
Acoustic absorption index	Sound absorption AW ^{a)}		
Direct airborne sound insulation index	Air flow resistivity AFR ^{a)}	NPD	
Continuous glowing combustion	Continuous glowing combustion	NPD	
Release of dangerous substances to the indoor environment	Release of dangerous substances	NPD	

¹⁾ No performance determined (NPD); ²⁾ no change with time; ^{a)} "i" indicates relevant class of level or declared value;

Table 2

d_N (mm)	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100	105	110	115	120	125
R_0 (m ² K/W)	0,55	0,65	0,80	0,95	1,10	1,25	1,35	1,50	1,65	1,80	1,90	2,05	2,20	2,35	2,50	2,60	2,75	2,90	3,05	3,15	3,30	3,45
d_N (mm)	130	135	140	145	150	155	160	165	170	175	180	185	190	195	200	-	-	-	-	-	-	-
R_0 (m ² K/W)	3,60	3,75	3,85	4,00	4,15	4,30	4,40	4,55	4,70	4,85	5,00	5,10	5,25	5,40	5,55	-	-	-	-	-	-	-

This declaration of performance is available on the website dop.rockwool.com

The performance of the product identified above is in conformity with the set of declared performance. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Halina Ozon

Cigacice, 2020-05-20

