

**DECLARATION OF PERFORMANCE**  
**No RW-CEE-DoP-0115/CM/20/w1**

- |  |   |
|--|---|
| <p>1. Unique identification code of the product-type:<br/><b>RW-CEE-0115</b></p> <p>2. Intended use/es: <b>Thermal Insulation products for buildings (THIB).</b></p> <p>3. Manufacturer: <b>ROCKWOOL® Polska Sp. z o.o.,<br/>ul. Kwiatowa 14, 66-131 Cigacice.</b></p> | <p>4. System/s of AVCP: <b>System 1 and System 3</b><br/>Harmonised standard: <b>EN 13162:2012+A1:2015</b></p> <p>5. Notified body No <b>1390</b></p> <p>6. Declared Performance/s: in the Table 1 and Table 2:</p> |
|--|---|

Table 1

Essential Characteristics	Performance	Declared value / NPD <sup>1)</sup>	Harmonized technical specification
Thermal resistance	Thermal resistance $R_0$ and $d_N$ thermal conductivity $\lambda_D$	see Table 2 0,038 W/mK	EN 13162:2012+A1:2015
	Ti <sup>a)</sup> Thickness	T4	
Reaction to fire	Euroclasses – Reaction to fire (RtF) product	A1	
Durability of reaction to fire against heat, weathering, ageing/ degradation	Durability characteristics Reaction to fire (RtF) product <sup>2)</sup>	A1	
Durability of thermal resistance against heat, weathering, ageing/ degradation	Thermal resistance $R_0$ and thermal conductivity $\lambda_D$ (W/mK) <sup>2)</sup>	see Table 2 0,038 W/mK	
	Durability characteristics	DS(70,-) DS(70,90)	
Compressive strength	Compressive stress CS(10) <sup>3)</sup> , CS(10/Y) <sup>3)</sup> (kPa)	CS(10)40* *)for top layer CS(10)70	
	Point load PL(5) <sup>3)</sup> (N)	PL(5)650	
Tensile / Flexural strength	Tensile strength perpendicular to faces TR <sup>3)</sup> (kPa)	TR10	
Durability of compressive strength against ageing/ degradation	Compressive creep	NPD	
Water permeability	Short term water absorption WS ( $\leq 1$ kg/m <sup>2</sup> )	WS	
	Long term water absorption WL(P) ( $\leq 3$ kg/m <sup>2</sup> )	WL(P)	
Water vapour permeability	Water vapour transmission	MU1	
	Water vapour diffusion resistance factor		
Impact noise transmission index (for floors)	Dynamic stiffness SD <sup>3)</sup>	NPD	
	Thickness, $d_L$	NPD	
	Compressibility c	NPD	
	Air flow resistivity AFri <sup>3)</sup>	NPD	
Acoustic absorption index	Sound absorption AW <sup>3)</sup>	NPD	
Direct airborne sound insulation index	Air flow resistivity AFri <sup>3)</sup>	NPD	
Continuous glowing combustion	Continuous glowing combustion	NPD	
Release of dangerous substances to the indoor environment	Release of dangerous substances	NPD	

<sup>1)</sup> No performance determined (NPD); <sup>2)</sup> no change with time; <sup>3)</sup> \* indicates relevant class of level or declared value;

Table 2

$d_N$ (mm)	50	60	70	80	90	100	110	120	130	140	150	160	170	180	190	200	210	220	230	240	250	-
$R_0$ (m <sup>2</sup> K/W)	1,30	1,55	1,80	2,10	2,35	2,60	2,85	3,15	3,40	3,65	3,90	4,20	4,45	4,70	5,00	5,25	5,50	5,75	6,05	6,30	6,55	-

This declaration of performance is available on the website [dop.rockwool.com](http://dop.rockwool.com)

The performance of the product identified above is in conformity with the set of declared performance. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Halina Ozon

Cigacice, 2020-07-26

*Halina Ozon*