

## DECLARATION OF PERFORMANCE

### No RW-CEE-DoP-0655/CM/20/w1

- |   |   |
|---|---|
| <b>1.</b> Unique identification code of the product-type:<br><b>RW-CEE-0655</b>                         | <b>4.</b> System/s of AVCP: <b>System 1 and System 3</b><br><br>Harmonised standard: <b>EN 13162:2012+A1:2015</b> |
| <b>2.</b> Intended use/es: <b>Thermal Insulation products for buildings (ThiB).</b>                     | <b>5.</b> Notified body No <b>1390</b>  |
| <b>3.</b> Manufacturer: <b>ROCKWOOL® Polska Sp. z o.o.,</b><br><b>ul. Kwiatowa 14, 66-131 Cigacice.</b> | <b>6.</b> Declared Performance/s: in the Table 1 and Table 2  |

**Table 1**

Essential Characteristics	Performance	Declared value / NPD <sup>1)</sup>	Harmonized technical specification
Thermal resistance	Thermal resistance $R_0$ and $d_N$ thermal conductivity $\lambda_D$	see Table 2 0,036 W/mK	EN 13162:2012+A1:2015
	Ti <sup>a)</sup> Thickness	T3	
Reaction to fire	Euroclasses – Reaction to fire (RtF) product	A1	
Durability of reaction to fire against heat, weathering, ageing/ degradation	Durability characteristics Reaction to fire (RtF) product <sup>2)</sup>	A1	
Durability of thermal resistance against heat, weathering, ageing/ degradation	Thermal resistance $R_0$ and thermal conductivity $\lambda_D$ (W/mK) <sup>2)</sup>	see Table 2 0,036 W/mK	
	Durability characteristics	NPD	
Compressive strength	Compressive stress CS(10) <sup>a)</sup> , CS(10/Y) <sup>a)</sup> (kPa)	NPD	
	Point load PL(5) <sup>a)</sup> (N)	NPD	
Tensile / Flexural strength	Tensile strength perpendicular to faces TR <sub>0</sub> <sup>a)</sup> (kPa)	NPD	
Durability of compressive strength against ageing/ degradation	Compressive creep	NPD	
Water permeability	Short term water absorption WS ( $\leq 1$ kg/m <sup>2</sup> )	WS	
	Long term water absorption WL(P) ( $\leq 3$ kg/m <sup>2</sup> )	NPD	
Water vapour permeability	Water vapour transmission Water vapour diffusion resistance factor	MU1	
Impact noise transmission index (for floors)	Dynamic stiffness SD <sub>i</sub> <sup>a)</sup> Thickness, $d_L$ Compressibility $c$ Air flow resistivity AFR <sub>i</sub> <sup>a)</sup>	NPD NPD NPD NPD	
Acoustic absorption index	Sound absorption AW <sub>i</sub> <sup>a)</sup>	NPD	
Direct airborne sound insulation index	Air flow resistivity AFR <sub>a</sub> <sup>a)</sup>	NPD	
Continuous glowing combustion	Continuous glowing combustion	NPD	
Release of dangerous substances to the indoor environment	Release of dangerous substances	NPD	

<sup>1)</sup> No performance determined (NPD); <sup>2)</sup> no change with time; <sup>a)</sup> \* indicates relevant class of level or declared value;

**Table 2**

$d_N$ (mm)	15	20	30	40	50	60	70	80	90	100	110	120	130	140	150	160	170	180	190	200	-	-
$R_0$ (m <sup>2</sup> K/W)	0,40	0,55	0,80	1,10	1,35	1,65	1,90	2,20	2,50	2,75	3,05	3,30	3,60	3,85	4,15	4,40	4,70	5,00	5,25	5,55	-	-

This declaration of performance is available on the website [dop.rockwool.com](http://dop.rockwool.com)

The performance of the product identified above is in conformity with the set of declared performance. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Halina Ozon

Cigacice, 2020-06-20

