

DECLARATION OF PERFORMANCE

No RW-CEE-DoP-0659/CM/24/w1

- | | |
|---|--|
| <p>1. Unique identification code of the product-type:
RW-CEE-0659</p> <p>2. Intended use/es: Thermal insulation products for buildings (ThIB).</p> <p>3. Manufacturer: ROCKWOOL® Polska Sp. z o.o.,
ul. Kwiatowa 14, 66-131 Cigacice.</p> | <p>4. System/s of AVCP: System 1 and System 3</p> <p>Harmonised standard: EN 13162:2012+A1:2015</p> <p>5. Notified body No 1023</p> <p>6. Declared Performance/s: in the Table 1 and Table 2:</p> |
|---|--|

Table 1

Essential Characteristics	Performance	Declared value / NPD ¹⁾	Harmonized technical specification
Thermal resistance	Thermal resistance R _D and d _N thermal conductivity λ _D	see Table 2 0,038 W/mK	EN 13162:2012+A1:2015
	Ti ^{a)} Thickness	T5	
Reaction to fire	Euroclasses – Reaction to fire (RtF) product	A1	
Durability of reaction to fire against heat, weathering, ageing/ degradation	Durability characteristics Reaction to fire (RtF) product ²⁾	A1	
Durability of thermal resistance against heat, weathering, ageing/ degradation	Thermal resistance R _D and thermal conductivity λ _D (W/mK) ²⁾	see Table 2 0,038 W/mK	
	Durability characteristics	NPD	
Compressive strength	Compressive stress CS(10) ⁱ ^{a)} , CS(10/Y) ⁱ ^{a)} (kPa)	NPD	
	Point load PL(5) ⁱ ^{a)} (N)	NPD	
Tensile / Flexural strength	Tensile strength perpendicular to faces TR ⁱ ^{a)} (kPa)	NPD	
Durability of compressive strength against ageing/ degradation	Compressive creep	NPD	
Water permeability	Short term water absorption WS (≤1 kg/m ²)	NPD	
	Long term water absorption WL(P) (≤ 3 kg/m ²)	NPD	
Water vapour permeability	Water vapour transmission Water vapour diffusion resistance factor	NPD	
Impact noise transmission index (for floors)	Dynamic stiffness SD ⁱ ^{a)}	NPD	
	Thickness, d _L	NPD	
	Compressibility c	NPD	
	Air flow resistivity AF ⁱ ^{a)}	NPD	
Acoustic absorption index	Sound absorption AW ⁱ ^{a)}	NPD	
Direct airborne sound insulation index	Air flow resistivity AF ⁱ ^{a)}	NPD	
Continuous glowing combustion	Continuous glowing combustion	NPD	
Release of dangerous substances to the indoor environment	Release of dangerous substances	NPD	

¹⁾ No performance determined (NPD); ²⁾ no change with time; ^{a)} "T" indicates relevant class of level or declared value;


Table 2

d_N (mm)	40	80	100	102	103	122	150	180	200	202	232	240	-	-	-	-	-	-	-	-	-	-
R_D (m ² K/W)	1,05	2,10	2,60	2,65	2,70	3,20	3,90	4,70	5,25	5,30	6,10	6,30	-	-	-	-	-	-	-	-	-	-

This declaration of performance is available on the website dop.rockwool.com

The performance of the product identified above is in conformity with the set of declared performance. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Halina Ozon

Cigacice, dnia 12-04-2024