

## DECLARATION OF PERFORMANCE

### No RW-CEE-DoP-0661/CM/24/w1

- |  |  |
|--|--|
| <p>1. Unique identification code of the product-type:<br/><b>RW-CEE-0661</b></p> <p>2. Intended use/es: <b>Thermal insulation products for buildings (ThIB).</b></p> <p>3. Manufacturer: <b>ROCKWOOL® Polska Sp. z o.o.,<br/>ul. Kwiatowa 14, 66-131 Cigacice.</b></p> | <p>4. System/s of AVCP: <b>System 1 and System 3</b></p> <p>Harmonised standard: <b>EN 13162:2012+A1:2015</b></p> <p>5. Notified body No <b>1023</b></p> <p>6. Declared Performance/s: in the Table 1 and Table 2:</p> |
|--|--|

**Table 1**

Essential Characteristics	Performance	Declared value / NPD <sup>1)</sup>	Harmonized technical specification
Thermal resistance	Thermal resistance R <sub>D</sub> and d <sub>N</sub> thermal conductivity λ <sub>D</sub>	see Table 2 0,038 W/mK	EN 13162:2012+A1:2015
	Ti <sup>a)</sup> Thickness	T5	
Reaction to fire	Euroclasses – Reaction to fire (RtF) product	A1	
Durability of reaction to fire against heat, weathering, ageing/ degradation	Durability characteristics Reaction to fire (RtF) product <sup>2)</sup>	A1	
Durability of thermal resistance against heat, weathering, ageing/ degradation	Thermal resistance R <sub>D</sub> and thermal conductivity λ <sub>D</sub> (W/mK) <sup>2)</sup>	see Table 2 0,038 W/mK	
	Durability characteristics	NPD	
Compressive strength	Compressive stress CS(10) <sup>i</sup> <sup>a)</sup> , CS(10/Y) <sup>i</sup> <sup>a)</sup> (kPa)	NPD	
	Point load PL(5) <sup>i</sup> <sup>a)</sup> (N)	NPD	
Tensile / Flexural strength	Tensile strength perpendicular to faces TR <sup>i</sup> <sup>a)</sup> (kPa)	NPD	
Durability of compressive strength against ageing/ degradation	Compressive creep	NPD	
Water permeability	Short term water absorption WS (≤1 kg/m <sup>2</sup> )	NPD	
	Long term water absorption WL(P) (≤ 3 kg/m <sup>2</sup> )	NPD	
Water vapour permeability	Water vapour transmission Water vapour diffusion resistance factor	NPD	
Impact noise transmission index (for floors)	Dynamic stiffness SD <sup>i</sup> <sup>a)</sup>	NPD	
	Thickness, d <sub>L</sub>	NPD	
	Compressibility c	NPD	
	Air flow resistivity AF <sup>i</sup> <sup>a)</sup>	NPD	
Acoustic absorption index	Sound absorption AW <sup>i</sup> <sup>a)</sup>	NPD	
Direct airborne sound insulation index	Air flow resistivity AF <sup>i</sup> <sup>a)</sup>	NPD	
Continuous glowing combustion	Continuous glowing combustion	NPD	
Release of dangerous substances to the indoor environment	Release of dangerous substances	NPD	

<sup>1)</sup> No performance determined (NPD); <sup>2)</sup> no change with time; <sup>a)</sup> "T" indicates relevant class of level or declared value;

**Table 2**

$d_N$ (mm)	40	80	100	102	108	117	128	130	150	162	170	200	220	230	232	240	-	-	-	-	-	-
$R_D$ (m <sup>2</sup> /KW)	1,05	2,10	2,60	2,65	2,80	3,05	3,35	3,40	3,90	4,25	4,45	5,25	5,75	6,05	6,10	6,30	-	-	-	-	-	-

This declaration of performance is available on the website [dop.rockwool.com](http://dop.rockwool.com)

The performance of the product identified above is in conformity with the set of declared performance. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Halina Ozon

Cigacice, dnia 12-04-2024