

## DECLARATION OF PERFORMANCE

### No RW-CEE-DoP-0664/CM/24/w1

- |   |   |
|---|---|
| <b>1.</b> Unique identification code of the product-type:<br><b>RW-CEE-0664</b>                   | <b>4.</b> System/s of AVCP: <b>System 1 and System 3</b><br><br>Harmonised standard: <b>EN 13162:2012+A1:2015</b> |
| <b>2.</b> Intended use/es: <b>Thermal insulation products for buildings (ThIB).</b>               | <b>5.</b> Notified body No <b>1023</b>  |
| <b>3.</b> Manufacturer: <b>ROCKWOOL® Polska Sp. z o.o.,<br/>ul. Kwiatowa 14, 66-131 Cigacice.</b> | <b>6.</b> Declared Performance/s: in the Table 1 and Table 2:   |

**Table 1**

Essential Characteristics	Performance	Declared value / NPD <sup>1)</sup>	Harmonized technical specification
Thermal resistance	Thermal resistance R <sub>D</sub> and d <sub>N</sub> thermal conductivity λ <sub>D</sub>	see Table 2 0,040 W/mK	EN 13162:2012+A1:2015
	Ti <sup>a)</sup> Thickness	T5	
Reaction to fire	Euroclasses – Reaction to fire (RtF) product	A1	
Durability of reaction to fire against heat, weathering, ageing/ degradation	Durability characteristics Reaction to fire (RtF) product <sup>2)</sup>	A1	
Durability of thermal resistance against heat, weathering, ageing/ degradation	Thermal resistance R <sub>D</sub> and thermal conductivity λ <sub>D</sub> (W/mK) <sup>2)</sup>	see Table 2 0,040 W/mK	
	Durability characteristics	NPD	
Compressive strength	Compressive stress CS(10) <sup>i</sup> <sup>a)</sup> , CS(10/Y) <sup>i</sup> <sup>a)</sup> (kPa)	NPD	
	Point load PL(5) <sup>i</sup> <sup>a)</sup> (N)	NPD	
Tensile / Flexural strength	Tensile strength perpendicular to faces TR <sup>i</sup> <sup>a)</sup> (kPa)	NPD	
Durability of compressive strength against ageing/ degradation	Compressive creep	NPD	
Water permeability	Short term water absorption WS (≤1 kg/m <sup>2</sup> )	NPD	
	Long term water absorption WL(P) (≤ 3 kg/m <sup>2</sup> )	NPD	
Water vapour permeability	Water vapour transmission Water vapour diffusion resistance factor	NPD	
Impact noise transmission index (for floors)	Dynamic stiffness SD <sup>i</sup> <sup>a)</sup>	NPD	
	Thickness, d <sub>L</sub>	NPD	
	Compressibility c	NPD	
	Air flow resistivity AF <sup>i</sup> <sup>a)</sup>	NPD	
Acoustic absorption index	Sound absorption AW <sup>i</sup> <sup>a)</sup>	NPD	
Direct airborne sound insulation index	Air flow resistivity AF <sup>i</sup> <sup>a)</sup>	NPD	
Continuous glowing combustion	Continuous glowing combustion	NPD	
Release of dangerous substances to the indoor environment	Release of dangerous substances	NPD	

<sup>1)</sup> No performance determined (NPD); <sup>2)</sup> no change with time; <sup>a)</sup> "T" indicates relevant class of level or declared value;

**Table 2**

$d_N$ (mm)	40	80	100	102	103	120	129	130	150	180	200	202	220	230	232	240	-	-	-	-	-	-
$R_D$ (m <sup>2</sup> K/W)	1,00	2,00	2,50	2,55	2,55	3,00	3,20	3,25	3,75	4,50	5,00	5,05	5,50	5,75	5,80	6,00	-	-	-	-	-	-

This declaration of performance is available on the website [dop.rockwool.com](http://dop.rockwool.com)

The performance of the product identified above is in conformity with the set of declared performance. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Halina Ozon

Cigacice, dnia 12-04-2024