

Declaration of Performance No RW-CEE-DoP-0832/B/24/w1

- | | |
|---|--|
| <p>1. Unique identification code of the product-type:
RW-CEE-0832</p> <p>2. Intended use: thermal insulation products for building equipment.</p> <p>3. Manufacturer: ROCKWOOL Polska Sp. z o.o.
ul.Kwiatowa 14, 66-131 Cigacice</p> | <p>4. System of attestation of conformity: System 1 and System 3</p> <p>5. Harmonised standard: EN 14303:2009+A1:2013
Notified body No. 0751 Forschungsinstitut für Wärmeschutz e.V.
München</p> <p>6. Declared Performance in the Table 1 and Table 2:</p> |
|---|--|

Table 1

Essential characteristics		Performance		Declared value/ NPD ¹⁾				Harmonized technical specification
Thermal resistance	Thermal conductivity	Temperature	θ (°C)	40	50	100	150	EN 14303:2009+A1:2013
		Curve 0	λ _D (W/mK)	0,035	0,037	0,044	0,052	
		Temperature	θ (°C)	10	50	100	150	
		Curve 1	λ _D (W/mK)	0,034	0,039	0,046	0,056	
	Thickness	Inside diameter <i>D_i</i> , thickness <i>d_D</i> <i>T_i</i> thickness tolerances : - outside diameter <i>D₀</i> < 150 mm - outside diameter <i>D₀</i> ≥ 150 mm		Table 2 T8 T9				
Reaction to fire		Euroclass - reaction to fire (RtF) - <i>D₀</i> ≤ 300mm i <i>d_D</i> ≥20mm		A2L-s1, d0				
Durability of thermal resistance against ageing/degradation		Maximum service temperature 250°C		ST(+)250				
Durability of thermal resistance against high temperature		Maximum service temperature 250°C		ST(+)250				
Durability of reaction to fire against ageing/ degradation		Durability characteristics - reaction to fire (RtF): <i>D₀</i> ≤ 300mm i <i>d_D</i> ≥20mm		A2L-s1, d0				
Durability of reaction to fire against high temperature		Durability characteristics - reaction to fire (RtF): <i>D₀</i> ≤ 300mm i <i>d_D</i> ≥20mm		A2L-s1, d0				
Compressive strength		Compressive strength at 10% deformation CS(10) _i ²⁾		NPD				
Water permeability		Water absorption (≤ 1 kg/m ²)		WS1				
Water vapour permeability		Water vapour diffusion equivalent air layer thickness, MV _i ²⁾		MV2				
Rate of release of corrosive substances		Trace quantities of water-soluble chloride ions ≤ 10ppm pHi ²⁾ -value		CL10 NPD				
Acoustic absorption index		Sound absorption (AW _i ²⁾)		NPD				
Release of dangerous substances to the indoor environment		Release of dangerous substances		NPD				
Continuous glowing combustion		Continuous glowing combustion		NPD				

¹⁾ NPD=No performance determined;

²⁾ "i" indicates relevant class of level or declared value

Table 2

D_i^*/d_b^{**}	Curve λ	D_i^*/d_b^{**}	Curve λ	D_i^*/d_b^{**}	Curve λ
15/20	0	35/20	0	54/20	0
15/30	0	35/30	0	54/30	0
15/40	0	35/40	0	54/40	0
18/20	0	35/60	1	54/50	0
18/30	0	42/20	0	60/20	0
18/40	0	42/30	0	60/30	0
22/20	0	42/40	0	60/40	0
22/30	0	42/50	0	60/50	0
22/40	0	42/60	1	64/20	0
22/50	1	48/20	0	64/30	0
22/60	1	48/30	0	64/40	0
28/20	0	48/40	0	64/50	0
28/30	0	48/50	0	76/30	0
28/40	0	48/60	1	76/40	0
28/50	1			89/30	0
28/60	1				

*) D_i - inside diameter;

**) d_b nominal thickness


This declaration of performance is available on the website dop.rockwool.com

The performance of the product identified above is in conformity with the set of declared performance. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Halina Ozon
Central Service Department Manager
(name, function)

Cigacice 2024-07-31
(Place, date)



(Signature)