

DECLARATION OF PERFORMANCE
RW-PL/G-DoP-/T/1007/24/w1

- | | | | |
|----|--|----|--|
| 1. | Unique identification code of the product-type:
RW-PL-G-1007-I | 4. | System/s of AVCP: System 1 and System 3 |
| 2. | Intended use: Thermal insulation products for buildings (ThiB). | 5. | Harmonised standard: EN 13162:2012+A1:2015
Notified body No: Építéssügyi Minőségellenőrző Innovációs Nonprofit Kft. (1415). |
| 3. | Manufacturer: ROCKWOOL® Hungary Kft., H-8300 Tapolca, Keszthelyi út 53. | 6. | Declared Performance in the Table 1 and Table 2:
MW-EN 13162-T4-DS(70,90)-WS-WL(P)-AF12-MU1 |

Table 1

Essential Characteristics	Performance	Declared value / NPD ¹⁾	Harmonized technical specification
Thermal resistance	Thermal resistance R ₀ and thermal conductivity λ _D	see Table 2 0,035 W/mK	EN 13162:2012+A1:2015
	TI ^{a)} Thickness	T4	
Reaction to fire	Euroclasses – reaction to fire (RtF) product	A1	
Durability of reaction to fire against heat, weathering, ageing/ degradation ²⁾	Durability characteristics Reaction to fire (RtF) product	A1	
Durability of thermal resistance against heat, weathering, ageing/ degradation ²⁾	Thermal resistance R ₀ and thermal conductivity λ _D (W/mK)	see Table 2 0,035 W/mK	
	Durability characteristics	NPD	
		DS(70,90)	
Compressive strength	Compressive stress CS(10) _i ^{a)} , CS(10/Y) _i ^{a)} (kPa)	NPD	
	Point load PL(5) _i ^{a)} (N)	NPD	
Tensile / Flexural strength	Tensile strength perpendicular to faces TRI ^{a)} (kPa)	NPD	
Durability of compressive strength against ageing/ degradation	Compressive creep	NPD	
Water permeability	Short term water absorption WS (≤1 kg/m ²)	WS	
	Long term water absorption WL(P) (≤ 3 kg/m ²)	WL(P)	
Water vapour permeability	Water vapour transmission Water vapour diffusion resistance factor	MU1	
Impact noise transmission index (for floors)	Dynamic stiffness SD _i ^{a)} Thickness, d _L Compressibility c Air flow resistivity AF _n ^{a)}	NPD NPD NPD AF12	
Acoustic absorption index	Sound absorption AW _i ^{a)}	NPD	
Direct airborne sound insulation index	Air flow resistivity AF _n ^{a)}	AF12	
Continuous glowing combustion	Continuous glowing combustion	NPD	
Release of dangerous substances to the indoor environment	Release of dangerous substances to the indoor environment	NPD	

¹⁾ No performance determined (NPD); ²⁾ no change with time; a) "i" indicates relevant class of level or declared value;

Table 2

Thermal resistance, R_D ,																			
d(mm)	20	30	40	50	60	70	80	90	100	110	120	130	140	150	160	170	180	190	200
$R_D(m^2K/W)$	-	0,85	1,10	1,40	1,70	2,00	2,25	2,55	2,85	3,10	3,40	3,70	4,00	4,25	4,55	4,85	5,10	5,40	5,70

NOTE: R value for thickness not seen in Table 2, is available on product label
This declaration of performance is available on the website dop.rockwool.com

d(mm)	220
$R_D(m^2K/W)$	6,25

NOTE: R value for thickness not seen in Table 2, is available on product label
This declaration of performance is available on the website dop.rockwool.com

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

Katalin Pál
Quality assurance and Environmental Manager

(Name, function)

Tapolca, 27.06.2024.

(Place, date)

ROCKWOOL® Hungary Kft.
H-8300 Tapolca,
Keszthelyi út. 53.
Magyarország

Pat Kate
(Signature)

(Signature _____)

1415-CPR-9-(C-7/2010)