

1. Unique identification code of the product-type	RWUK-CE-0080-05_english
2. Intended use of the construction product as foreseen by the manufacturer, in accordance with the applicable harmonised technical specification	Thermal insulation for buildings (ThIB)
3. Name, registered trade name or registered trademark and contact address of the manufacturer, as required pursuant to Article 11(5) of regulation (EU) No 305/2011	ROCKWOOL® Limited Pencoed, Bridgend, CF35 6NY, UK
4. Name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2) of regulation (EU) No 305/2011	ROCKWOOL® FRANCE S.A.S. 111 rue du Château des Rentiers, 75013 Paris, France. dop.eu@rockwool.com
5. Applicable System or Systems of Assessment and Verification of Constancy of Performance (AVCP)	SYSTEM 1 for uses subject to regulations on reaction to fire SYSTEM 3 for all other intended uses
6. Harmonised Standard reference number	EN 13162:2012+A1:2015
7. Notified Body identification number	0751
8. Declared Performances	Please refer to TABLE 1 and TABLE 2

TABLE 1

Essential Characteristics	Clauses in this European Standard related to essential characteristics	Level and/or classes	Declared value
Thermal resistance	4.2.1 Thermal resistance and thermal conductivity	Declared R_D and λ_D	R_D : See TABLE 2 λ_D : <90mm thick = 0.034 W/mK ≥90mm thick = 0.035 W/mK
	4.2.3 Thickness	Declared d and T	Thickness range: 50mm-230mm Tolerance Class: T4
Reaction to fire Euroclass characteristics	4.2.6 Reaction to fire	Euroclasses	A1
Durability of reaction to fire against heat, weathering, ageing/degradation	4.2.7 Durability characteristics ^{a)}	Euroclasses	A1 ^{a)}
Durability of thermal resistance against heat, weathering, ageing/degradation	4.2.1 Thermal resistance and thermal conductivity ^{b)}	Declared R_D and λ_D	R_D : See TABLE 2 λ_D : <90mm thick = 0.034 W/mK ≥90mm thick = 0.035 W/mK
	4.2.7 Durability characteristics ^{c)}	Declared DS	NPD ^{c)}
Compressive strength	4.3.3 Compressive stress or compressive strength	Declared CS Level	NPD
	4.3.5 Point load	Declared PL	NPD
Tensile/Flexural strength	4.3.4 Tensile strength perpendicular to faces ^{d)}	Declared TR Level	NPD ^{d)}
Durability of compressive strength against ageing/degradation	4.3.6 Compressive creep	Declared CC	NPD
Water permeability	4.3.7.1 Short term water absorption	Declared WS	WS
	4.3.7.2 Long term water absorption	Declared $WL(P)$	$WL(P)$
Water vapour permeability	4.3.8 Water vapour transmission	Declared MU or Z	NPD
Impact noise transmission index (for floors)	4.3.9 Dynamic stiffness	Declared SD	NPD
	4.3.10.2 Thickness, d_L	Declared d_L and T Class	NPD
	4.3.10.4 Compressibility ^{c)}	Declared CP	NPD
	4.3.12 Air flow resistivity	Declared AF_r	NPD
Acoustic absorption index	4.3.11 Sound absorption	Declared AP and AW	NPD
Direct airborne sound insulation index	4.3.12 Air flow resistivity	Declared AF_r	NPD
Release of dangerous substances to the indoor environment	4.3.13 Release of dangerous substances ^{e)}		NPD ^{e)}
Continuous glowing combustion	4.3.15 Continuous glowing combustion ^{e)}		NPD ^{e)}

NPD - No Performance Determined

^{a)} No change in reaction to fire properties for mineral wool products. The fire performance of mineral wool does not deteriorate with time. The Euroclass classification of the product is related to the organic content, which cannot increase with time.

^{b)} Thermal conductivity of mineral wool products does not change with time; experience has shown the fibre structure to be stable and the porosity contains no other gases than atmospheric air.

^{c)} For dimensional stability thickness only.

^{d)} This characteristic also covers handling and installation.

^{e)} European test methods are under development.


TABLE 2

Thermal Resistance, R _D																
Thickness, d (mm) *	50	55	60	65	70	75	80	85	90	95	100	105	110	115	120	125
R _D (m ² K/W)	1.45	1.60	1.75	1.90	2.05	2.20	2.35	2.50	2.55	2.70	2.85	3.00	3.10	3.25	3.40	3.55
Thickness, d (mm) *	130	135	140	145	150	155	160	165	170	175	180	185	190	195	200	205
R _D (m ² K/W)	3.70	3.85	4.00	4.10	4.25	4.40	4.55	4.70	4.85	5.00	5.10	5.25	5.40	5.55	5.70	5.85
Thickness, d (mm) *	210	215	220	225	230											
R _D (m ² K/W)	6.00	6.10	6.25	6.40	6.55											

* Please note that the availability of any of the above thicknesses are subject to confirmation from your ROCKWOOL representative.

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Marion Davies
Technical Director

At Bridgend on 12th June 2025